

## JETTING DUCT LUBE

**Duct Lube** is a special lubricant for ducts from 16 mm inside diameter and up, used previous to blowing of fibre and cables.

**Duct Lube** is water based and can be used down to -15 degrees C. It leaves a very tiny film of lubricant, reduces drastically the friction, static electricity, and adheres perfectly to the cable and to the duct surface. It's a water emulsion of different kind of polymers.

**Duct Lube** is white with a tiny viscosity.

### Suggest Uses quantities for 1.000 mt

diam Ø mm internal pipe	Quantities of product
20 – 30 mm	600 ml
30 - 40 mm	700 ml
40 - 50 mm	1000 ml

### Use:

- 1- Clean the inside of the duct by blowing a sponge slowly thru the duct.
- 2- Shake the bottle before using.
- 3- Pre lubricate by:
  - Place a sponge as far into the duct according to the table on the bottle.
  - Fill the suggested lubricant into the duct.
  - Place one or two sponges in the end and blow this thru slowly.
- 4-The duct is now ready for fibre / cable blowing.

### Technical Specifications:

Aspect	White liquid tiny viscosity
Odour	none
Viscosity	120 sec. Ford cup diam. mm 4 at 20C°
Specific gravity	1,030 +- 0,03 gr/cm <sup>3</sup>
pH	7,5 +- 0,5
Inflammability	non infiammabile
Temperature	-15° + 70° C.
Biodegradability	yes
Toxic	The product is not toxic.
HS Code	3403.9900
Country of origin	Italy
Art. No	34031