



Professional Office/Contact Centre Headsets



Technical Data

Impedance:	2.2kΩ
Sensitivity:	-32dB ± 3dB at 1kHz
Directivity:	Bi-directional
Frequency Range:	50Hz~20kHz ± 6dB
Distortion:	Less than 3%
Power Supply:	3V DC
S/N Ratio:	More than 58dB

Speaker:	
Impedance:	150Ω ± 15% at 1kHz
Sensitivity:	93 ± 3dB at 1kHz 60mV Input
Max Input Power:	100mV
Frequency Range:	100Hz~6,800Hz
Distortion:	Less 3% at 1kHz 60mV







PLX COMPATIBLE

CLOTHING CLIP & HANGING HOOK

HEADSET CASE









JPL-611

Featuring a contact centre designed microphone boom arm with improved clarity and noise cancelling.

Overview

Features	Single or dual ear	
	Left / right ear side compatible	
	Surround Shield™ noise cancelling microphone with static shock protection	
	Wideband enabled speakers with Sound Shield™ acoustic shock protection	
	'Put and stay' ratchet microphone boom arm	
	Overhead, sure-fit fully adjustable headband with optional padded headband for additional comfort	
	Fitted with large 50mm leatherette ear cushions for maximum all day comfort	
What's included	Headset Tough Case, headset hanging hook, Clothing clip and Quick Start Guide	
Headset Weight	~62g/~94g	
Connection	PLX fitted as standard or GN** compatible QD options	
Compatibility	For full range of bottom leads* and compatibility information - Go to Jpltele.com	
Certifications	UKCA, CE, FCC, EAN, RoHS, REACH	
Warranty	3 Years Warranty - includes 2 years standard no quibble repair or replace warranty PLUS a 3rd year cover on all non-moving parts	
MOQ	Master Shipping Carton: 32	
EAN:	JPL-611-PM: 5060126956822, JPL-611-PB: 5060126956839	
SKU:	JPL-611-PM: 575-121-001, JPL-611-PB: 575-121-002	

PLX = Plantronics compatible QD E&OE



 * optional to purchase seperately.

 ** GN QD available on special request